

Praxair Material Safety Data Sheet

1. Chemical Product and Company Identification

Product Name: Oxygen, compressed (MSDS No. P-4638-E)	Trade Name: Oxygen, Medipure™ Oxygen
Chemical Name: Oxygen	Synonyms: Dioxygen
Formula: O ₂	Chemical Family: Permanent gas
Telephone:	Company Name: Praxair, Inc. 39 Old Ridgebury Road Danbury, CT 06810-5113
Emergencies: 1-800-645-4633*	
CHEMTREC: 1-800-424-9300*	
Routine: 1-800-PRAXAIR	

* Call emergency numbers 24 hours a day only for spills, leaks, fire, exposure, or accidents involving this product. For routine information, contact your supplier, Praxair sales representative, or call 1-800-PRAXAIR (1-800-772-9247).

2. Composition/Information on Ingredients

This section covers materials of manufacture only. See sections 3, 8, 10, 11, 15, and 16 for information on by-products generated during use, especially use in welding and cutting. See section 16 for important information about mixtures.

INGREDIENT	CAS NUMBER	CONCENTRATION	OSHA PEL	ACGIH TLV-TWA (2002)
Oxygen	7782-44-7	>99%*	None currently established	None currently established

*The symbol > means "greater than."

3. Hazards Identification

EMERGENCY OVERVIEW

**WARNING! High-pressure, oxidizing gas.
Vigorously accelerates combustion.
Self-contained breathing apparatus may be required by rescue workers.
Odor: None**

THRESHOLD LIMIT VALUE: None currently established. ACGIH, 2002, recommends a TLV-TWA of 5 mg/m³ for welding fumes not otherwise classified (NOC) that may be generated during welding with this product. See section 16 for more information on welding hazards. TLV-TWAs should be used as a guide in the control of health hazards and not as fine lines between safe and dangerous concentrations.

EFFECTS OF A SINGLE (ACUTE) OVEREXPOSURE:

INHALATION—Breathing 80% or more oxygen at atmospheric pressure for more than a few hours may cause nasal stuffiness, cough, sore throat, chest pain, and breathing difficulty. Breathing oxygen at higher pressure increases the likelihood of adverse effects within a shorter time period. Breathing pure oxygen under pressure may cause lung damage and also Central Nervous System (CNS) effects resulting in dizziness, poor coordination, tingling sensation, visual and hearing disturbances, muscular twitching, unconsciousness, and convulsions. Breathing oxygen under pressure may cause prolongation of adaptation to darkness and reduced peripheral vision.

SKIN CONTACT—No harm expected.

SWALLOWING—This product is a gas at normal temperature and pressure.

EYE CONTACT—No harm expected.

EFFECTS OF REPEATED (CHRONIC) OVEREXPOSURE: No harm expected.

OTHER EFFECTS OF OVEREXPOSURE: See section 11, Toxicological Information.

MEDICAL CONDITIONS AGGRAVATED BY OVEREXPOSURE: See section 11, Toxicological Information.

SIGNIFICANT LABORATORY DATA WITH POSSIBLE RELEVANCE TO HUMAN HEALTH HAZARD EVALUATION: None known.

CARCINOGENICITY: Oxygen is not listed by NTP, OSHA, or IARC.

4. First Aid Measures

INHALATION: Immediately remove to fresh air. If not breathing, give artificial respiration. Keep victim warm and at rest. Call a physician. Advise the physician that the victim has been exposed to a high concentration of oxygen.

SKIN CONTACT: Wash with soap and water; seek medical attention if discomfort persists.

SWALLOWING: This product is a gas at normal temperature and pressure.

EYE CONTACT: Flush eyes thoroughly with water. Hold the eyelids open and away from the eyeballs to ensure that all surfaces are flushed thoroughly. Get medical attention if discomfort persists.

NOTES TO PHYSICIAN: Supportive treatment should include immediate sedation, anti-convulsive therapy if needed, and rest. See section 11, Toxicological Information.

5. Fire Fighting Measures

FLASH POINT (test method):	Not applicable
AUTOIGNITION TEMPERATURE:	Not applicable
FLAMMABLE LIMITS IN AIR , % by volume:	LOWER: Not applicable UPPER: Not applicable

EXTINGUISHING MEDIA: Vigorously accelerates combustion. Use media appropriate for surrounding fire. Water (e.g., safety shower) is the preferred extinguishing method for clothing fires.

SPECIAL FIRE FIGHTING PROCEDURES: WARNING! High-pressure, oxidizing gas. Evacuate all personnel from danger area. Immediately deluge cylinders with water from maximum distance until cool; then move them away from fire area if without risk. Self-contained breathing apparatus may be required by rescue workers. On-site fire brigades must comply with OSHA 29 CFR 1910.156.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Oxidizing agent; vigorously accelerates combustion. Contact with flammable materials may cause fire or explosion. Heat of fire can build pressure in cylinder and cause it to rupture. Oxygen cylinders are equipped with a pressure relief device. (Exceptions may exist where authorized by DOT.) No part of cylinder should be subjected to a temperature higher than 125°F (52°C). Smoking, flames, and electric sparks in the presence of enriched oxygen atmospheres are potential explosion hazards.

HAZARDOUS COMBUSTION PRODUCTS: None known.

6. Accidental Release Measures

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: WARNING! High-pressure, oxidizing, gas. Shut off flow if without risk. Ventilate area or move cylinder to a well-ventilated area. Remove all flammable materials from vicinity. Oxygen must never be permitted to strike an oily surface, greasy clothes, or other combustible material.

WASTE DISPOSAL METHOD: Prevent waste from contaminating the surrounding environment. Keep personnel away. Discard any product, residue, disposable container, or liner in an environmentally acceptable manner, in full compliance with federal, state, and local regulations. If necessary, call your local supplier for assistance.

7. Handling and Storage

PRECAUTIONS TO BE TAKEN IN STORAGE: Store and use with adequate ventilation, away from oil, grease, and other hydrocarbons. Separate oxygen cylinders from flammables by at least 20 ft (6.1 m) or use a barricade of noncombustible material. This barricade should be at least 5 ft (1.53 m) high and have a fire resistance rating of at least ½ hour. Firmly secure cylinders upright to keep them from falling or being knocked over. Screw valve protection cap firmly in place by hand. Store only where temperature will not exceed 125°F (52°C). Store full and empty cylinders separately. Use a first-in, first-out inventory system to prevent storing full cylinders for long periods.

PRECAUTIONS TO BE TAKEN IN HANDLING: Protect cylinders from damage. Use a suitable hand truck to move cylinders; do not drag, roll, slide, or drop. Never attempt to lift a cylinder by its cap; the cap is intended solely to protect the valve. Never insert an object (e.g., wrench, screwdriver, pry bar) into cap openings; doing so may damage the valve and cause a leak. Use an adjustable strap wrench to remove over-tight or rusted caps. Open valve slowly. If valve is hard to open, discontinue use and contact your supplier. Never apply flame or localized heat directly to any part of the cylinder. High temperatures may damage the cylinder and could cause the pressure relief device to fail prematurely, venting the cylinder contents. For other precautions in using this mixture, see section 16.

For additional information on storage and handling, refer to Compressed Gas Association (CGA) pamphlet P-1, *Safe Handling of Compressed Gases in Containers*, available from the CGA. Refer to section 16 for the address and phone number along with a list of other available publications.

8. Exposure Controls/Personal Protection

VENTILATION/ENGINEERING CONTROLS:

LOCAL EXHAUST—Use a local exhaust system, if necessary, to prevent increased oxygen concentration and, in welding, to keep hazardous fumes and gases below applicable TLVs in the worker's breathing zone.

MECHANICAL (general)—General exhaust ventilation may be acceptable if it can maintain a supply of air that is not too rich in oxygen and, during welding, can keep hazardous fumes and gases below applicable TLVs in the worker's breathing zone.

SPECIAL—None

OTHER—None

RESPIRATORY PROTECTION: None required under normal use. However, air-supplied respirators are required while working in confined spaces with this product. For welding, use air-purifying or air-supplied respirators, as appropriate, where local or general exhaust ventilation is inadequate. Adequate ventilation must keep worker exposure below applicable TLVs for fumes, gases, and other by-products of welding with oxygen. See sections 3, 10, and 16 for details. The respiratory protection used must conform with OSHA rules as specified in 29 CFR 1910.134.

SKIN PROTECTION: Wear work gloves when handling cylinders; welding gloves for welding. Gloves must be free of oil and grease.

EYE PROTECTION: Wear safety glasses when handling cylinders. For welding, wear goggles with filter lens selected as per ANSI Z49.1. Provide protective screens and goggles, if necessary, to protect others. Select as per OSHA 29 CFR 1910.33

OTHER PROTECTIVE EQUIPMENT: Metatarsal shoes for cylinder handling. Select in accordance with OSHA 29 CFR 1910.132 and 1910.133. As needed for welding, wear hand, head, and body protection to help prevent injury from radiation and sparks. (See ANSI Z49.1.) At a minimum, this includes welder's gloves and protective goggles, and may include arm protectors, aprons, hats, shoulder protection, as well as substantial clothing. Regardless of protective equipment, never touch live electrical parts.

9. Physical and Chemical Properties

MOLECULAR WEIGHT:	31.9988
SPECIFIC GRAVITY (Air = 1) at 70°F (21.1°C) and 1 atm:	1.105
SOLUBILITY IN WATER , vol/vol at 32°F (0°C):	0.0489
PERCENT VOLATILES BY VOLUME:	100
BOILING POINT at 1 atm:	-297.4°F (-183°C)
FREEZING POINT at 1 atm:	-361.1°F (-218.4°C)

APPEARANCE, ODOR, AND STATE: Colorless, odorless, tasteless gas at normal temperature and pressure.

10. Stability and Reactivity**STABILITY:** Unstable Stable**INCOMPATIBILITY (materials to avoid):** Combustible materials, asphalt, flammable materials, especially oils and greases. Oxygen reacts with many materials.**HAZARDOUS DECOMPOSITION PRODUCTS:** None known.**HAZARDOUS POLYMERIZATION:** May Occur Will Not Occur**CONDITIONS TO AVOID:** None known.**11. Toxicological Information**

The welding process may generate hazardous fumes and gases. (See sections 3, 10, 15, and 16.)

At atmospheric concentration and pressure, oxygen poses no toxicity hazards. At high concentrations, newborn premature infants may suffer delayed retinal damage (retrolental fibroplasia) that can progress to retinal detachment and blindness. Retinal damage may also occur in adults exposed to 100% oxygen for extended periods (24 to 48 hours) or at pressures exceeding atmospheric pressure, particularly in individuals whose retinal circulation has been previously compromised. All individuals exposed for long periods to oxygen at high pressure and all who exhibit overt oxygen toxicity should have ophthalmologic examinations.

At two or more atmospheres, CNS toxicity occurs. Symptoms include nausea, vomiting, dizziness or vertigo, muscle twitching, vision changes, and loss of consciousness and generalized seizures. At three atmospheres, CNS toxicity occurs in less than two hours; at six atmospheres, in only a few minutes.

Patients with chronic obstructive pulmonary disease retain carbon dioxide abnormally. If oxygen is administered, raising their blood-oxygen concentration, their breathing becomes depressed and retained carbon dioxide rises to a dangerous level.

Animal studies suggest that the administration of certain drugs, including phenothiazine drugs and chloroquine, increases the susceptibility to toxicity from oxygen at high concentrations or pressures. Animal studies also indicate that vitamin E deficiency may increase susceptibility to oxygen toxicity.

Airway obstruction during high oxygen tension may cause alveolar collapse following absorption of the oxygen. Similarly, occlusion of the eustachian tubes may cause retraction of the eardrum and obstruction of the paranasal sinuses may produce vacuum-type headache.

12. Ecological Information

No adverse ecological effects expected. Oxygen does not contain any Class I or Class II ozone-depleting chemicals. Oxygen is not listed as a marine pollutant by DOT.

13. Disposal Considerations

WASTE DISPOSAL METHOD: Do not attempt to dispose of residual or unused quantities. Return cylinder to supplier. For emergency disposal, secure cylinder in a well-ventilated area or outdoors; then slowly discharge gas to the atmosphere.

14. Transport Information

DOT/IMO SHIPPING NAME: Oxygen, compressed

HAZARD CLASS: 2.2	IDENTIFICATION NUMBER: UN 1072	PRODUCT RQ: None
--------------------------	---------------------------------------	-------------------------

SHIPPING LABEL(s): OXYGEN. An oxygen label may be used for domestic shipment in the United States and Canada in place of the NONFLAMMABLE GAS and OXIDIZER labels (49 CFR Part 172).

PLACARD (when required): NONFLAMMABLE GAS or OXYGEN

SPECIAL SHIPPING INFORMATION: Cylinders should be transported in a secure position, in a well-ventilated vehicle. Cylinders transported in an enclosed, nonventilated compartment of a vehicle can present serious safety hazards.

Shipment of compressed gas cylinders that have been filled without the owner's consent is a violation of federal law [49 CFR 173.301(b)].

15. Regulatory Information

The following selected regulatory requirements may apply to this product. Not all such requirements are identified. Users of this product are solely responsible for compliance with all applicable federal, state, and local regulations.

U.S. FEDERAL REGULATIONS:

EPA (ENVIRONMENTAL PROTECTION AGENCY)

CERCLA: COMPREHENSIVE ENVIRONMENTAL RESPONSE, COMPENSATION, AND LIABILITY ACT OF 1980 (40 CFR Parts 117 and 302):

Reportable Quantity (RQ): None

SARA: SUPERFUND AMENDMENT AND REAUTHORIZATION ACT:

SECTIONS 302/304: Require emergency planning based on Threshold Planning Quantity (TPQ) and release reporting based on Reportable Quantities (RQ) of Extremely Hazardous Substances (EHS) (40 CFR Part 355):

Threshold Planning Quantity (TPQ): None

EHS RQ (40 CFR 355): None

SECTIONS 311/312: Require submission of MSDSs and reporting of chemical inventories with identification of EPA hazard categories. The hazard categories for this product are as follows:

IMMEDIATE: No

PRESSURE: Yes

DELAYED: No

REACTIVITY: No

FIRE: Yes

SECTION 313: Requires submission of annual reports of release of toxic chemicals that appear in 40 CFR Part 372.

Oxygen does not require reporting under Section 313.

40 CFR 68: RISK MANAGEMENT PROGRAM FOR CHEMICAL ACCIDENTAL RELEASE PREVENTION: Requires development and implementation of risk management programs at facilities that manufacture, use, store, or otherwise handle regulated substances in quantities that exceed specified thresholds.

Oxygen is not listed as a regulated substance.

TSCA: TOXIC SUBSTANCES CONTROL ACT: Oxygen is listed on the TSCA inventory.

OSHA: OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION:

29 CFR 1910.119: PROCESS SAFETY MANAGEMENT OF HIGHLY HAZARDOUS CHEMICALS: Requires facilities to develop a process safety management program based on Threshold Quantities (TQ) of highly hazardous chemicals.

Oxygen is not listed in Appendix A as a highly hazardous chemical.

STATE REGULATIONS:

CALIFORNIA: Oxygen is not listed by California under the SAFE DRINKING WATER AND TOXIC ENFORCEMENT ACT OF 1986 (Proposition 65).

PENNSYLVANIA: Oxygen is subject to the PENNSYLVANIA WORKER AND COMMUNITY RIGHT-TO-KNOW ACT (35 P.S. Sections 7301-7320).

16. Other Information

Be sure to read and understand all labels and instructions supplied with all containers of this product.

WARNING: Medical grades of oxygen are subject to strict federal regulations and are for use only under the control of a licensed physician or clinician familiar with the product and its hazards.

ADDITIONAL SAFETY AND HEALTH HAZARDS: *High-pressure, oxidizing gas.* Clean all gauges, valves, regulators, piping, and equipment to be used in oxygen service in accordance with CGA pamphlet G-4.1. Keep cylinders and their valves free of oil and grease. Use piping and equipment adequately designed to withstand pressures to be encountered. Close cylinder valve after each use; keep closed even when empty. *Never use oxygen as a substitute for compressed air.* Never use an oxygen jet for cleaning purposes of any sort, especially for clothing. Oxygen increases the likelihood of an engulfing fire. *Never work on a pressurized system.* If a leak occurs, close the cylinder valve. Blow the system down in a safe and environmentally sound manner in compliance with all federal, state, and local laws; then repair the leak. *Never place a compressed gas cylinder where it may become part of an electrical circuit.*

Personnel who have been exposed to high concentrations of oxygen should stay in a well-ventilated or open area before going into a confined space or near an ignition source.

SPECIAL PRECAUTIONS: *Use in welding and cutting.* Read and understand the manufacturer's instructions and the precautionary label on the product. See American Standard Z49.1, *Safety in Welding and Cutting*, published by the American Welding Society, PO Box 351040, Miami, FL 33135, and OSHA Publication 2206 (29CFR 1910), US Government Printing Office, Washington, DC 20402, for more information.

Arcs and sparks can ignite combustible materials. Prevent fires. Refer to NFPA 51B, *Cutting and Welding Processes*. *Do not strike an arc on the cylinder.* The defect produced by an arc burn could lead to cylinder rupture.

MIXTURES: When you mix two or more gases or liquefied gases, you can create additional, unexpected hazards. Obtain and evaluate the safety information for each component before you produce the mixture. Consult an industrial hygienist or other trained person when you evaluate the end product. Remember, gases and liquids have properties that can cause serious injury or death.

HAZARD RATING SYSTEMS:**NFPA RATINGS:**

HEALTH	= 0
FLAMMABILITY	= 0
INSTABILITY	= 0
SPECIAL	= OX (OXidizer)

HMIS RATINGS:

HEALTH	= 0
FLAMMABILITY	= 0
PHYSICAL HAZARD	= 0

STANDARD VALVE CONNECTIONS FOR U.S. AND CANADA:

THREADED:	0-3000 psig	CGA-540
	3001-4000 psig	CGA-577
	4001-5500 psig	CGA-701
PIN-INDEXED YOKE:	0-3000 psig	CGA-870 (Medical Use)
ULTRA-HIGH-INTEGRITY CONNECTION:	0-3000 psig	CGA-714

Use the proper CGA connections. **DO NOT USE ADAPTERS.**

Ask your supplier about free Praxair safety literature as referred to in this MSDS and on the label for this product. Further information about this product can be found in the following pamphlets published by the Compressed Gas Association, Inc. (CGA), 4221 Walney Road, 5th Floor, Chantilly, VA 20151-2923, Telephone (703) 788-2700.

AV-1	<i>Safe Handling and Storage of Compressed Gases</i>
AV-8	<i>Characteristics and Safe Handling of Cryogenic Liquid and Gaseous Oxygen</i>
G-4	<i>Oxygen</i>
G-4.1	<i>Cleaning Equipment for Oxygen Service</i>
P-1	<i>Safe Handling of Compressed Gases in Containers</i>
P-2	<i>Characteristics and Safe Handling of Medical Gases</i>
P-14	<i>Accident Prevention in Oxygen-Rich, Oxygen-Deficient Atmospheres</i>
SB-2	<i>Oxygen-Deficient Atmospheres</i>
SB-8	<i>Use of Oxy-Fuel Gas Welding and Cutting Apparatus</i>
V-1	<i>Compressed Gas Cylinder Valve Inlet and Outlet Connections</i>
—	<i>Handbook of Compressed Gases, Fourth Edition</i>

Praxair asks users of this product to study this MSDS and become aware of product hazards and safety information. To promote safe use of this product, a user should (1) notify employees, agents, and contractors of the information in this MSDS and of any other known product hazards and safety information, (2) furnish this information to each purchaser of the product, and (3) ask each purchaser to notify its employees and customers of the product hazards and safety information.

The opinions expressed herein are those of qualified experts within Praxair, Inc. We believe that the information contained herein is current as of the date of this Material Safety Data Sheet. Since the use of this information and the conditions of use of the product are not within the control of Praxair, Inc., it is the user's obligation to determine the conditions of safe use of the product.

Praxair MSDSs are furnished on sale or delivery by Praxair or the independent distributors and suppliers who package and sell our products. To obtain current Praxair MSDSs for these products, contact your Praxair sales representative or local distributor or supplier. If you have questions regarding Praxair MSDSs, would like the form number and date of the latest MSDS, or would like the names of the Praxair suppliers in your area, phone or write the Praxair Call Center (**Phone:** 1-800-PRAXAIR; **Address:** Praxair Call Center, Praxair, Inc., PO Box 44, Tonawanda, NY 14151-0044).

Praxair, the *Flowing Airstream* design, and *Medipure* are trademarks or registered trademarks of Praxair Technology, Inc. in the United States and other countries.



Praxair, Inc.
39 Old Ridgebury Road
Danbury, CT 06810-5113